

SWIR

fxo992MCX

The SWIR cameras based on the EXO and FXO series offer an extremely wide usable spectral range of 400-1700nm with the Sony SenSWIR sensor. Highly efficient thermal management of the housing is the basis of the outstanding dynamic range and homogeneity of the image. The integrated 4-channel strobe controller supports complex illumination and analysis scenarios.

Technical Highlights

- Switchable active cooling (FXO only)
- GenICam 3.0, GenTL
- Integrated 4-channel LED strobe controller
- I/O interface with 2xIN, 4xOUT, Opto and RS232
- programmable timer, logic functions and sequencer

ATTENTION: This product is subject to export control and requires written information on intended use and final destination!



Specifications

Resolution [MP]	5.2 MP
Resolution (h x v)	2560 x 2048 px
Frame rate(max.)	132.6 fps
Chroma	SWIR
Interface	CXP-12 with 1 Connection (micro-BNC)

Sensor

Sensor	IMX992-AABJ
Manufacturer	Sony
Sensor type	Area SWIR CMOS
Shutter type	global shutter
Sensor size (h x v)	8.83 x 7.07 mm
Optical diagonal	11.31 mm
Sensor format	11.4mm (Type 1/1.4)
Pixel size (h x v)	3.45 x 3.45 µm

Camera

Exposure modes	MANUAL;AUTO
Trigger modes	INTERNAL;SOFTWARE;EXTERNAL
Pixel format / max	mono8, mono10, mono12 / 12 bit
Gain modes	manual, auto
Internal memory	1024 MB SDRAM, 32 MB Flash

Feature Set

AOI	yes
LUT	yes
Offset	yes
Binning	yes
Image flip	yes
Two-Point NUC	yes
Defect pixel correction	yes
Sequencer	yes


Housing

Lens mount	C-Mount
Dimensions (w x h x d)	50 x 50 x 70.1 mm
Weight	240 g
Operating temperature (housing)	-10 to 60 °C
Protection class	IP30


I/O-Interfaces

Input up to 24V	2 x
Input OPTO	1 x
Output open drain	4 x
I/O RS-232	1 x
Power supply	10 to 25 V (DC)
Power consumption	7 W (dep. on operating mode)


front




back




cross section




right side




top



bottom




3D



Pinout Mating Connector

Hirose 12 Pin	1 VIN - (GND)	7 OUT 1 (open drain)
	2 VIN + (10 V to 25 V DC)	8 OUT 2 (open drain)
	3 IN 4 (RXD RS232)	9 IN 3 + (opto In +)
	4 OUT 4 (TXD RS232)	10 IN 3 - (opto In -)
	5 IN 1 (0 - 24V)	11 OUT 3 (open drain)
	6 IN 2 (0 - 24V)	12 OUT 0 (open drain)

Spectral Response *



* Sensor data – excludes camera cover- or IR-cut filter characteristics

